





Coolants & screenwash - Cooling fluids

# **Eurol Coolant -36°C GLX**

## Silicate-free, long-life coolant TL-VW 774 F (G12+)

### Description

Eurol Coolant -36 GLX has especially been developed for the new generation cooling systems of modern car engines.

Eurol Coolant -36 GLX, based on ethylene-glycol, has been approved by Volkswagen (TL 774 D) and meets the Renault D standard.

Eurol Coolant -36 GLX prevents scale forming and offers excellent protection against cavitation. Moreover, it protects all metals against corrosion, particularly aluminum and alloy irons, even at high temperatures.

Eurol Coolant -36 GLX protects against freezing up to -36 °C and contains environment-friendly additives (carboxyl-acids). This technology is known under the name OAT (Organic-Acid-Technology).

Eurol Coolant -36 GLX is to be used undiluted, so never top-up with pure water. Life-time of the product is 5 years or 650.000 kms for trucks or 250.000 kms for passenger cars, depending on which situation occurs

#### **Specifications**

Performance level VW TL-774 F (G12+) VW TL-774 D (G12) BS 6580 ASTM D4985 ASTM D4656 ASTM D3306 Renault Type D NATO S-759 JASO M325

#### **Physical properties**

Colour	Pink	
Density at 20°C	1.069 kg/l	ASTM D 1298
Frost protection	-36 °C	ASTM D 1177

first.

Eurol Coolant -36 GLX is nitrite, amine, borate, phosphate, nitrate and silicate free. The product is compatible with traditional coolants of traditional quality.

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.