



**Mounting Suggestions**  
**Harley-Davidson® Softail 200mm Wide Tire Models**  
**2006-11 FXST**  
**2007-11 FLSTF Fatboy**  
**2008-11 FLSTSB Crossbones**  
**2007-10 FXSTC Softail Custom**  
**2010-11 FLSTFB Fatboy LO**  
**One-Piece Seat**



**Baseplate Features:**

**Mustang Softail seats will NOT fit 1999-earlier FLSTS Heritage Springers.** All seats are built on 16 gauge formed steel baseplates. A welded nose tab clips into the frame mount behind the gas tank. The baseplates have rubber supports at contact points and carpet to protect the fender.

**Note: On Crossbones models, springs and frame cover must be removed before installing Mustang seat.**

**Removal of Stock Seat**

1. Remove rear fender screw.
2. Pull seat back and up to remove from bike.
3. If passenger handstrap is present, remove it before installing Mustang seat.

**Installation of Mustang One-Piece Seat**

1. Engage nose tab at front of seat.
2. Align rear tab and insert stock 1/4-20 fender screw.



These steps are guidelines to help you install your new Mustang Product. If you need further assistance, please call us at 800-243-1392 or 860-582-9633, Monday through Friday 9:00 – 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under [“Support”](#).

Refers to part numbers: 75588, 76364, 76386, 76388, 76389, 76390, 76400, 76401, 76403, 76404, 76405